

Forklift Seat Belts

Seat Belt for Forklifts - This guideline reason is to be able to describe the Regulation requirements for the application of operator restraints or seatbelts on lift trucks. It is the employers' accountability to be able to ensure that every machine, piece of equipment and device inside the workplace is chosen and utilized properly and worked according to the manufacturer's directions.

Rough Terrain lift trucks need to meet the guidelines of ANSI Standard ASME B56.6-1992 regarding their use, design, maintenance, inspection and fabrication.

Mobile machinery like for instance side boom tractors with a Rollover Protective Structure (ROPS), must include seat belts that meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile equipment has seat belts required by law, the operator and subsequent passengers ought to make certain they use the belts whenever the motor vehicle is in motion or engaged in operation in view of the fact that this can cause the machine to become unsteady and hence, not safe.

If a seat belt or different driver restraint is needed on a lift truck.

While working a lift truck, the seat belt requirements will depend on some factors. Contributing factors to this determination may include whether the the lift truck is equipped along with a Rollover Protective Structure, the type of forklift itself and the year the forklift was actually made. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, system, or enclosure. A driver restraint device, enclosure or system is intended to be able to help the driver in lessening the possibility of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device could consist of a seat belt, even if a seat belt is not necessarily a part of such machine or system.